

C-UNO-2053E-ACP

Thin Client Solutions



Features

- Onboard AMD GX2 400 MHz fan-less processor, 256MB RAM
- -10-55C temperature range
- UL and CE certification
- DIN Rail mounting option
- Polarity protection
- RoHS compliant
- 10-30 VDC
- Small form factor
- Dual standard RS-232 and DB-15 VGA connector
- Dual 10/100 Base-T RJ-45 Port
- Two USB and one Type I/II PC cards
- Audio Line Out

Introduction

Advantech has improved "The Brick" with the UNO-2053E-ACP thin client. The cast aluminum housing provides a rugged chassis with improved thermal characteristics. Wide input power range of 10-30 VDC, polarity protection allows the use of power supplies commonly used in industrial applications. The UNO-2053E-ACP has rich video display characteristics supporting high color and resolution.

Specifications

- CPU AMD GX-2 400 MHz
- Memory 256 DDR SDRAM
- Audio Line Out
- VGA/Keyboard.Mouse DB-15 VGA connector, PS/2 keyboard & mouse
- Video Support CRT 1920 x 1440
- Serial Port 2 x standard RS-232
- Speed RE-232 50 ~ 115.2 Kbps
- USB Interface 2x USB Ports, USB Open HCI, Rev. 1.0 compliant
- LAN Two 10/100 Base-R RJ-45 ports
- LED Power LED, IDE LED and one programmable diagnostic LED and buzzer
- Anti-Shock 20 G @ DIN IEC 68 section 2-27, half sine, 11ms 50 G @ Wall/Panel IEC 68 section 2-27, half sine, 11 ms
- Anti-Vibration 2 G @ IEC 68 section 2-6, sine, 5~500 Hz, 1 Oct./min, 1hr/axis
- Operating Temperature -10 ~ 55 C @ 5 ~ 85% relative humidity
- Relative Humidity 95% @ 40 C
- Power Input 9-36 VDC
- Chassis Size 7.5" x 4.2" x 1.4"
- Weight 0.8 kg

Ordering Information

- C-UNO-2053E-ACP GX2 400 M, 256 MB RAM C-UNO-2053E-ACP
- C-UNO-2053E-PS-ACP Thin Client with Power Supply

Accessories:

- PWR-DC24-50 Optional Power Supply
- PWR-242-A Optional Power Supply
- UNO-FPM21-AE UNO & FPM Integration Kit



ADVANTECH
eAutomation